

AquaRite® LT SV

EXPERT LINE



AN AFFORDABLE, HIGH QUALITY SALT CHLORINATOR WITH TRANSPARENT CELL

- **Automatic pH correction kit** available as an optional extra
- **Simple** to install, simple to use
- **Closed pool cover detection** for an instant reduction in chlorine production
- **Transparent cell** to enable a visual check of the production. Gas sensor included
- **Options available** for this easy-to-use salt chlorinator
- **Optional ORP kit** regulates the chlorine production



INCLUDED



Cl Production



ORP kit Standard probe (optional)



pH correction kit (optional)

AQUARITE® LT SV

| Description | AQR-LTO-SV16 | AQR-LTO-SV22 | AQR-LTO-SV33 | AQR-LTO-SV50 |
|---------------------------------------|---|--------------------|--------------------|--------------------|
| Maximum production Cl ₂ /h | 16 gr | 22 gr | 33 gr | 50 gr |
| Salt concentration | From 3gr up to 100 gr Na/Cl | | | |
| Pool volume | 75 m ³ | 100 m ³ | 150 m ³ | 250 m ³ |
| Display | 2,8" TFT | | | |
| Alimentation | 220V 50/60Hz | | | |
| Dimensions | 270 x 220 x 115 mm | | | |
| Electronic box | Fireproof black ABS plastic | | | |
| Front cover | Black ABS plastic | | | |
| Output | 8-15A | 8-20A | 10-15A | 35-45A |
| Consumption | 120W | 160W | 150W | 360W |
| pH control | Yes - Chip, pH probe, probe holder, peristaltic pump 1,5 L/h | | | |
| Temperature control | Yes | | | |
| Automatic cleaning | Operates by reverse polarity | | | |
| Salinity test via Wifi | Salinity detected in g/l (accuracy ±10%) | | | |
| Pool cover | Programmable 0 – 100% production as a function of pool cover being open or closed | | | |

TRANSPARENT CELL

| | | | | |
|--------------------------|----------------------------------|----------------------------------|----------------------------------|------------------------------|
| Electrolysis cell | 4 Titanium cell plates MONOPOLAR | 5 Titanium cell plates MONOPOLAR | 7 Titanium cell plates MONOPOLAR | 10 titanium plates MONOPOLAR |
| Minimum flow | 5 m ³ /h | 7 m ³ /h | 9 m ³ /h | 9 m ³ /h |
| Dimension cell plates | 200 x 45 mm | 200 x 45 mm | 200 x 45 mm | 400 x 45 mm |
| Material cell housing | Plastic PVC transparent | | | |
| Cell fastener | Thread for an easy installation | | | |
| Diameter tube connection | 63 mm | | | |
| Dimension cell | 355 x 305 x 305 mm | | | |
| Cell cable size | (3 x 4) x 1.5 m | | | |
| Gas sensor | Included in the cell | | | Flow switch |
| Maximum pressure | 4 kg/cm ² | | | |
| Maximum temperature | 45°C | | | |

AVAILABLE OPTIONS

| | |
|------------------------|-----------------|
| PH standard probe kit | BKPER-OPTION-PH |
| ORP standard probe kit | E-OPTION-REDOX |
| Flow switch | J-OPTION-FLOW |